

> 4T SERIES





中實動力夾頭(四爪高速中實型)

4-JAW NON THROUGH HOLE POWER CHUCK



It's applicable for clamping irregular shape parts

- ◎ 楔形四爪中實卡盤，特別適合异形物的夾持。
- ◎ 摺動面均經硬化及精密研磨，并直接潤滑。
- ◎ 高剛性結構及高夾持精度。
- ◎ It's a wedge four claws solid chuck.
- ◎ Matching surfaces of all parts hardened, ground and lubricated directly.
- ◎ Construction of high rigidity and high clamping accuracy.



規格 Spec 型號 Model	A	B	C(h6)	D	D1	D2	E	E1	F	G		H	J			
										Max	Min					
4T-06 A5	165	74	84	140	104.8	82.56	116	5	15	21	101.5	86.5	81.5	66.5	36	34
4T-08 A5	210	85	103	170	133.4	82.56	104.8	5	23	25	127	104	106	83	36	38
4T-08 A6	210	85	97	170	133.4	106.38	150	5	17	25	127	110	106	89	36	38
4T-10 A6	254	89	109	220	171.4	106.38	133.4	5	25	34	158	133	133	108	36	45
4T-10 A8	254	89	102	220	171.4	139.72	190	5	18	34	158	140	133	115	36	45
4T-12 A8	304	106	118	220	171.4	139.72	190	6	18	34	163	145	133	115	36	50
4T-15 A8	381	114	141	300	235	139.72	171.4	6	33	-	104	71	69	36	55	60
4T-15 A11	381	114	130	300	235	196.87	260	6	22	-	104	82	69	47	55	60

規格 Spec 型號 Model	L1	L2	M1	M2	M3	N	P	R		S	T	
								max	min			
4T-06 A5	14	14	39	M16×2	4-M10	4-M6	73	20	18	7.5	31	12
4T-08 A5	20	17	41	M20×2.5	4-M12	4-M10	95	25	22.3	11.8	35	14
4T-08 A6	20	18	41	M20×2.5	4-M12	4-M6	95	25	22.3	11.8	35	14
4T-10 A6	18	18	46	M20×2.5	4-M16	4-M12	110	30	30.8	11.3	40	16
4T-10 A8	18	25	46	M20×2.5	4-M16	4-M8	110	30	30.8	11.3	40	16
4T-12 A8	22	25	54	M20×2.5	4-M16	4-M8	130	30	48.8	12.3	50	18
4T-15 A8	30	29	63	M30×3.5	4-M20	4-M16	165	43	48.8	23.3	62	25.5
4T-15 A11	30	33	63	M30×3.5	4-M20	4-M10	165	43	48.8	23.3	62	25.5

規格 Spec 型號 Model	楔心套行程 Plunger stroke mm	卡爪行程(直徑) Jaw stroke(Dia.) mm	許用推拉力 Max. pull force KN(kgf)	最大夾緊力 Max. Gripping force KN(kgf)	極限轉速 Max. Speed r/min	夾緊範圍 Gripping range mm	慣量 Moment of inertial Kg.m ²	重量 Weight Kg	適用油缸 Matching cylinder	最大使用壓力 Max. pressure Mpa(kgf/cm ²)
4T-08 A5	21	9.7	25(2550)	74.5(7600)	4750	17-210	0.14	24 28	S-125	2.3 (23)
4T-08 A6	21	9.7	25(2550)	74.5(7600)	4750	17-210	0.14	24 27	S-125	2.6 (26)
4T-10 A6	25	8.8	28.9(2950)	107.8(11000)	4000	22-254	0.30	35 42	S-125	2.6 (26)
4T-10 A8	25	8.8	28.9(2950)	107.8(11000)	4000	22-254	0.30	35 40	S-125	2.6 (26)
4T-12 A8	30	10.5	41(4180)	155.8(15900)	3360	22-304	0.73	59 63	S-125	2.6 (26)
4T-15 A8	35	16	82(8360)	248.4(25350)	3000	50-381	1.95	100 114	S-200	3.2 (32)
4T-15 A11	35	16	82(8360)	248.4(25350)	3000	50-381	1.95	100 107	S-200	3.2 (32)

* 保留技術更改的權利，恕不另行通知 Subject to technology changes without prior information
* 非標需求可訂做 Non-standard requirements can be made

