



## JAP200氣壓筒夾夾頭 產品尺寸及性能規格

型號	JAP206-5C	JAP207-16C	JAP207-B42	JAP208-B60	JAP210-B80
尺寸圖	fig.1	fig.1	fig.2	fig.2	fig.2
A	168(6.61")	203(7.99")	197(7.76")	214(8.43")	247(9.72")
B	130(5.12")	160(6.30")	155(6.10")	170(6.69")	200(7.87")
C	26(1.02")	40(1.57")	42(1.65")	60(2.36")	80(3.15")
D	4.5(0.18")	4.5(0.18")	4.5(0.18")	4.5(0.18")	5.0(0.20")
E	101(3.98")	113(4.44")	138(5.43")	148(5.83")	151(5.94")
F	55(2.17")	65(2.56")	77(3.03")	85(3.35")	80(3.16")
G	116(4.57")	136(5.35")	146(5.76")	164(6.46")	197(7.76")
H (P.C.D.)	147(5.79")	176(6.93")	172(6.77")	186(7.32")	226(8.90")
安裝螺絲孔	4H-M8 (前鎖)	3H-M10 (前鎖)+ 3H-M10 (後鎖)	3H-M10 (前鎖)+ 3H-M10 (後鎖)	3H-M10 (前鎖)+ 3H-M10 (後鎖)	6H-M10 (前鎖)
工作筒夾	5C筒夾	16C筒夾	B42(DIN6343 173E)	B60(DIN6343 185E)	B80(DIN6343 193E)
最高轉速RPM	3600	2800	2500	2000	1500
工作氣壓	3-8kg/cm <sup>2</sup> (43-114psi)	3-8kg/cm <sup>2</sup> (43-114psi)	3-8kg/cm <sup>2</sup> (43-114psi)	3-8kg/cm <sup>2</sup> (43-114psi)	3-8kg/cm <sup>2</sup> (43-114psi)
最大夾持徑	26mm(1.02")	40mm(1.57")	42mm(1.65")	60mm(2.36")	80mm(3.15")
活塞面積	130cm <sup>2</sup> (20.2in <sup>2</sup> )	155cm <sup>2</sup> (24.0in <sup>2</sup> )	280cm <sup>2</sup> (43.4in <sup>2</sup> )	304cm <sup>2</sup> (47.6in <sup>2</sup> )	356cm <sup>2</sup> (55.2in <sup>2</sup> )
夾持力	3465kgf@7kg/cm <sup>2</sup> (7623lbf@100psi)	4078kgf@7kg/cm <sup>2</sup> (8971lbf@100psi)	4740kgf@7kg/cm <sup>2</sup> (10428lbf@100psi)	5150kgf@7kg/cm <sup>2</sup> (11330lbf@100psi)	6030kgf@7kg/cm <sup>2</sup> (12060lbf@100psi)
產品淨重	10kgs(22lbs)	14kgs(31lbs)	17kgs(37lbs)	21kgs(46lbs)	32kgs(71lbs)